

VTEX AXELKOPPLING JAW

Elastomer / klokkoppling

VTEX 38 G

Kopplingsgummi VTEX/ROTEX

- Gjutjärn eller aluminium
- Förborrade eller Taper Lock
- Vtex / Trasco / Rotex



Produktbeskrivning

Vtex vridflexibla axelkopplingar är elastomerkopplingar som har en kompakt design.

Trots låga vikter hos elastomerkopplingarna kan de överföra höga vridmoment.

De kompakta axelkopplingarna kännetecknas av lång livslängd och goda driftsegenskaper och kan kundanpassas enkelt.

Tack vare elastomeren (elastomerspindeln) mellan kopplingsnaven på axelkopplingarna dämpas stötar respektive vibrationer i driften.

[illegible]

CASIMIR GQ25

STEEL*

INTERPRETATION CODES

EXAMPLE

GET-**19A-24B** → HUB A • HUB B

GET-**19A-24H** → HUB B • HUB A

GET-**19A-24L** → 2 HUB A

GET-**24B-24D** → 2 HUB B

The characteristic size of the coupling is defined by the maximum diameter bore.

PART NUMBERS					
Coupling Type	Part Number HUB A	Part Number HUB B	Spider BLACK 92/19A spider	Spider YELLOW 92/19B spider	Polyethylene YELLOW spider 92/19L spider
GET-1-T-24A-28	02202400	02202400	02002410	02002411	02002412
GET-1-T-24B-32	02202420	02202440	02002410	02002411	02002412
GET-1-T-24C-36	02202440	02202460	02002410	02002411	02002412
GET-1-T-24D-40	02202460	02202480	02002410	02002411	02002412
GET-1-T-24E-45	02202480	02202500	02002410	02002411	02002412
GET-1-T-24F-50	02202500	02202520	02002410	02002411	02002412
GET-1-T-24G-55	02202520	02202540	02002410	02002411	02002412
GET-1-T-24H-60	02202540	02202560	02002410	02002411	02002412
GET-1-T-24I-65	02202560	02202580	02002410	02002411	02002412
GET-1-T-24J-70	02202580	02202600	02002410	02002411	02002412
GET-1-T-24K-75	02202600	02202620	02002410	02002411	02002412
GET-1-T-24L-80	02202620	02202640	02002410	02002411	02002412
GET-1-T-24M-85	02202640	02202660	02002410	02002411	02002412
GET-1-T-24N-90	02202660	02202680	02002410	02002411	02002412
GET-1-T-24O-95	02202680	02202700	02002410	02002411	02002412
GET-1-T-24P-100	02202700	02202720	02002410	02002411	02002412

MEASUREMENTS - WEIGHTS														
Coupling Type	Ø hub			Ø bore			Ø internal thread			Ø external thread			Weight kg	
	A	B	max	A	B	max	C	D	E	F	G	H	A-B	A-B
GET-1-T-24A-28	-	-	-	24	32	38	40	14	16	18	20	22	8,1	0,5
GET-1-T-24B-32	-	-	24	32	40	48	50	16	18	20	22	24	10,6	0,6
GET-1-T-24C-36	-	-	28	36	45	54	56	18	20	22	24	28	13,1	0,7
GET-1-T-24D-40	-	-	32	40	50	60	62	20	22	24	26	30	15,6	0,8
GET-1-T-24E-45	-	-	36	45	55	65	68	22	24	26	28	32	18,1	0,9
GET-1-T-24F-50	-	-	40	50	60	70	73	24	26	28	30	34	20,6	1,0
GET-1-T-24G-55	-	-	45	55	65	75	78	26	28	30	32	36	23,1	1,1
GET-1-T-24H-60	-	-	50	60	70	80	83	28	30	32	34	38	25,6	1,2
GET-1-T-24I-65	-	-	55	65	75	85	88	30	32	34	36	40	28,1	1,3
GET-1-T-24J-70	-	-	60	70	80	90	93	32	34	36	38	42	30,6	1,4
GET-1-T-24K-75	-	-	65	75	85	95	98	34	36	38	40	44	33,1	1,5
GET-1-T-24L-80	-	-	70	80	90	100	103	36	38	40	42	46	35,6	1,6
GET-1-T-24M-85	-	-	75	85	95	105	108	38	40	42	44	48	38,1	1,7
GET-1-T-24N-90	-	-	80	90	100	110	113	40	42	44	46	50	40,6	1,8
GET-1-T-24O-95	-	-	85	95	105	115	118	42	44	46	48	52	43,1	1,9
GET-1-T-24P-100	-	-	90	100	110	120	123	44	46	48	50	54	45,6	2,0