

VTEX AXELKOPPLING JAW

Elastomer / klokoppling

VTEX 55 E
Kopplingshalva VTEX/ROTEX



- Gjutjärn eller aluminium
- Förborrade eller Taper Lock
- Vtex / Trasco / Rotex

Produktbeskrivning

Vtex vridflexibla axelkopplingar är elastomerkopplingar som har en kompakt design.

Trots låga vikter hos elastomerkopplingarna kan de överföra höga vridmoment.

De kompakta axelkopplingarna kännetecknas av lång livslängd och goda driftsegenskaper och kan kundanpassas enkelt.

Tack vare elastomeren (elastomerspindeln) mellan kopplingsnaven på axelkopplingarna dämpas stötar respektive vibrationer i driften.

TEKNISK DATA

Bussning

2012

Max axelhål

50 mm

Vikt

2,42 kg

Ytterdiameter Dy

120 mm

CAST-IRON GG25		STEEL*	
INTERPRETATION CODES		INTERPRETATION CODES	
EXAMPLE GE-T 19A-24B = HUB A + HUB B GE-T 19A-24B = HUB B + HUB A GE-T 19A-19A = 2 HUB A GE-T 24B-24B = 2 HUB B		EXAMPLE GE-T 19A-24B = HUB A + HUB B GE-T 19A-24B = HUB B + HUB A GE-T 19A-19A = 2 HUB A GE-T 24B-24B = 2 HUB B	
The characteristic size of the coupling is defined by the maximum diameter bore.		The characteristic size of the coupling is defined by the maximum diameter bore.	
PART NUMBERS		PART NUMBERS	
COUPLING TYPE	PART NUMBER	COUPLING TYPE	PART NUMBER
GE-T 19A-24B	02002400	GE-T 19A-24B	02002400
GE-T 24A-32B	02002420	GE-T 24A-32B	02002420
GE-T 28A-38B	02002820	GE-T 28A-38B	02002820
GE-T 38A-45B	02003820	GE-T 38A-45B	02003820
GE-T 42A-55B	02004220	GE-T 42A-55B	02004220
GE-T 45A-60B	02004520	GE-T 45A-60B	02004520
GE-T 55A-70B	02005520	GE-T 55A-70B	02005520
GE-T 65A-75B	02006520	GE-T 65A-75B	02006520
GE-T 75A-90B	02007520	GE-T 75A-90B	02007520
GE-T 90A-100B	02009020	GE-T 90A-100B	02009020

CAST-IRON GG25		STEEL*	
INTERPRETATION CODES		INTERPRETATION CODES	
EXAMPLE GE-T 19A-24B = HUB A + HUB B GE-T 19A-24B = HUB B + HUB A GE-T 19A-19A = 2 HUB A GE-T 24B-24B = 2 HUB B		EXAMPLE GE-T 19A-24B = HUB A + HUB B GE-T 19A-24B = HUB B + HUB A GE-T 19A-19A = 2 HUB A GE-T 24B-24B = 2 HUB B	
The characteristic size of the coupling is defined by the maximum diameter bore.		The characteristic size of the coupling is defined by the maximum diameter bore.	
PART NUMBERS		PART NUMBERS	
COUPLING TYPE	PART NUMBER	COUPLING TYPE	PART NUMBER
GE-T 19A-24B	02002400	GE-T 19A-24B	02002400
GE-T 24A-32B	02002420	GE-T 24A-32B	02002420
GE-T 28A-38B	02002820	GE-T 28A-38B	02002820
GE-T 38A-45B	02003820	GE-T 38A-45B	02003820
GE-T 42A-55B	02004220	GE-T 42A-55B	02004220
GE-T 45A-60B	02004520	GE-T 45A-60B	02004520
GE-T 55A-70B	02005520	GE-T 55A-70B	02005520
GE-T 65A-75B	02006520	GE-T 65A-75B	02006520
GE-T 75A-90B	02007520	GE-T 75A-90B	02007520
GE-T 90A-100B	02009020	GE-T 90A-100B	02009020